










FORD FALCON - Utility

AU, BA - BF, FG Ute

Part and Location	Description	Approx Lift Heights	Part No.	Qty Per Vehicle
Shock Absorbers				
Front Strut			SAB28800	2 ea
			Gas Struts (AU I, II, III)	
			SAB36690	
	Gas Struts (BA to BF)			
Rear  (right angle pin)			SAB36660	2 ea
	Gas Shock Absorbers (AU to BF)			
Coil Springs				
Front			H/Duty coil available on request for the various models	1 pr
	Heavy Duty Coil Springs			
Leaf Springs				
Rear			FORD021	2 ea
	Heavy Duty 4 + 2 Leaf Springs (fixed end eye = 54mm I.D.)	25mm to 30mm		
Shackle Bush Kits				
Rear			BU744UK	1 kit
	Polyurethane Bush Kit (must use SSA bush kit with SSA springs & O.E. bushes with O.E. springs)			
U-Bolts				
Rear			UB458	4 ea
			UB453-1	
	Round Form U Bolts (With Nuts) UB458 = 190mm x 75mm 9/16" round OR UB453-1 = 215mm x 83mm 9/16" round			
Rear			SPS-FORD	2 pr
	U Bolt Sandwich Plates (sold in pairs)			
Polyair Springs				
Rear			PA85111	1 ea
	Polyair Bellows Kit	STD		

For Heavy Duty applications with loads between 600kg & 700kg the 2nd stage of the FORD021 leaf spring need to be recambered so that it has 15mm clearance from the front of primary spring and 30mm clearance at the rear of the spring.